

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 920 BOOTH RELEASE WB COATING
PRODUCT CODE: 920

HMIS CODES: H F R P
1 0 0 H

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: CARBIT PAINT COMPANY
ADDRESS: 927 W. BLACKHAWK STREET, CHICAGO, ILLINOIS 60622
EMERGENCY PHONE: INFOTRAC 800-5355053 **INFORMATION PHONE:** 312-280-2300
DATE REVISED : 09-01-06 **NAME OF PREPARER :** CARBIT PAINT CO.
REASON REVISED : UPDATE

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE		WEIGHT PERCENT
		ACGIH TLV	OSHA PEL	IDLH	mm Hg @	TEMP	
STRAIGHT RUN MIDDLE DISTILLATE	64741-44-2	5 ppm	NIA	NIA	0.0	100F	25
ORGANIC ACIDS	NA				N/A		< 5.0%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
OSHA=Occupational Safety and Health Administration. TLV=Threshold Limit Value. NIOSH=National Institute for Occupational Safety and Health Administration. IDLH=Immediately dangerous to life or health concentrations.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING POINT: 500 Deg F **SPECIFIC GRAVITY (H2O=1):** 0.9
VAPOR DENSITY: LIGHTER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
COATING V.O.C. : 4.60 LB/GL (552 G/L)
MATERIAL V.O.C.: 1.53 LB/GL (183 G/L)
SOLUBILITY IN WATER: DILUTABLE
APPEARANCE AND ODOR: CREAMY CONSISTENCY WITH A MILD ODOR.

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: 260 Deg F **METHOD USED:** OPEN CUP
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.7% **UPPER:** 6.0%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP. NORMAL FIRE FIGHTING PROCEDURES MAY BE USED.

UNUSUAL FIRE AND EXPLOSION HAZARDS

THIS MATERIAL WILL NOT IGNITE OR SUPPORT COMBUSTION UNLESS THE WATER HAS EVAPORATED. PLASTIC CONTAINER MAY BURN AND LEAK FROM THE HEAT OF A FIRE
IF TEMPERATURE EXCEEDS BOILING POINT OF WATER THIS PRODUCT MAY SPATTER.

