

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: 942 BRT.WHITE W.B. STRIPPABLE
PRODUCT CODE: 942

HMIS CODES: H F R P
1 0 0 D

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: CARBIT PAINT COMPANY
ADDRESS: 927 W. BLACKHAWK STREET, CHICAGO, ILLINOIS 60622
EMERGENCY PHONE: INFOTRAC 800-5355053 **INFORMATION PHONE:** 312-280-2300
DATE REVISED : 09-01-06 **NAME OF PREPARER :** GUSTAVO MARTINEZ
REASON REVISED : UPDATE

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		ACGIH TLV	OSHA PEL	IDLH		
TITANIUM DIOXIDE	13463-67-7				N/A	5

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
OSHA=Occupational Safety and Health Administration. TLV=Threshold Limit Value. NIOSH=National Institute for Occupational Safety and Health Administration. IDLH=Immediately dangerous to life or health concentrations.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING POINT: 212 Deg F **SPECIFIC GRAVITY (H2O=1):** 1.2
VAPOR DENSITY: LIGHTER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
COATING V.O.C. : 0.34 LB/GL (41 G/L)
MATERIAL V.O.C.: 0.16 LB/GL (19 G/L)
SOLUBILITY IN WATER: COMPLETELY MISCIBLE
APPEARANCE AND ODOR: CREAMY CONSISTENCY WITH A VERY MILD ODOR

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: NONE **METHOD USED:** SETAFLASH
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A **UPPER:** N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

WEAR SELF CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN ENCLOSED AREAS OR WHEN EXPOSURE TO SMOKE AND GASES COULD OCCUR. NORMAL FIRE FIGTHING PROCEDURE MAY BE USED.

UNUSUAL FIRE AND EXPLOSION HAZARDS

THIS PRODUCT IS AN AQUEOUS SYSTEM AND IS NOT A FIRE HAZARD AS SUPPLIED, BUT MAY SPATTER IF TEMPERATURE OF LIQUID EXCEEDS THE BOILING POINT OF WATER. AFTER WATER IS EVAPORATED, THE DRIED SOLIDS CAN BURN. IF SOLIDS IGNITE, TOXIC GASES WILL FORM PLASTIC CONTAINER MAY BURN AND LEAK IN HEAT OF FIRE, THIS PRODUCT WILL NOT SUPPORT COMBUSTION UNLESS WATER HAS EVAPORATED

